



**SEPTON 40mm F2
E-mount**

INSTRUCTION MANUAL

Voigtländer E-mount lenses are designed for use on E-mount camera bodies. The lens covers the full frame format. They are manually controlled lenses so the user sets focus and aperture - the built-in CPU will transmit the information to the camera body to give the user Exif data. Depending on the specifications of the camera it will also give data for Auto-lens-correction, 5 axis-Image Stabilization as well as Manual-Focus Assist. Aperture selection is in 1/3 stop increments.

Features of Voigtländer E-mount lens

- Built-in CPU for lens communication with body
- Covers Full Frame on E-mount camera bodies
- Optical design optimized for Digital Sensors
- All Metal Lens Barrel for long life
- Smooth Manual Focusing for Precise focus

Tips for lens care and safety

These tips are to protect the user from injury or damaging the lens.



WARNING

If the user ignores this warning and uses the equipment incorrectly, serious injuries and even death may be the result.



CAUTION

If the user ignores this caution sign it might result in injuries and damage the equipment.



WARNING

Never look directly at the sun with a photographic lens as this can damage your eyes.



CAUTION

Keep the lens, camera and accessories out of the reach of children.



CAUTION

Store the lens away from direct sunlight and always store the lens with lens-cap on. Failure to do so may create a fire.

Never touch the lens surface. In case it is dirty or dusty use commercial lens cleaner or appropriate lens cleaning cloth.

● How to attach/detach the lens

Please refer to the instruction manual for your camera for how to attach or detach the lens to or from the camera mount.

* Please make sure to set the power of the camera to "OFF".

Please hold Depth of Field Ring ⑫ to attach/detach the lens. To attach/detach the lens while holding other parts of the lens barrel can damage the lens.

● Attaching Lens Hood

Screw the Lens Hood ① to the front of the lens.

● Attaching Filter

1. Screw the filter (Ø52mm) to the front of the lens.
2. Screw the Lens Hood ① into the thread of the filter when using the Lens Hood ① together with the filter.

* Do not screw the filter into the thread of the Lens Hood ①. This may cause vignetting.

How CPU/Contact works

1. Exif Data

Picture can store the Exif data of lens.

(For example, if you use Voigtländer 40mm F2)

Lens	Voigtlander SEPTON 40mm F2
	* Description may be changed depending on camera's firmware version or other factors.
Focal length	40mm
Maximum Aperture	F2
Aperture	The aperture value you used to take the picture

* Some camera bodies can not transmit data correctly.

2. Lens Correction Data

The lens stores the data for lens correction. You can set Auto Lens Correction on camera bodies;

Fall off	Auto / Off
Chromatic Aberration	Auto / Off
Distortion	Auto / Off

* On some camera bodies, you can not choose Auto Lens Correction Mode. In that case, a setting depends on the camera.

3. Manual Focus Assist

Magnified Live View Image will be seen on the camera's LCD screen when the camera detects the Focus Ring rotation. You can choose duration of the mode by MENU of camera body. Please refer to the instruction manual of your camera.

* On some camera bodies, you can not use this function.

* Please set "MF Mode" to use this function.

4. Focus Distance Setting

Focus Distance Setting Indication can be seen on the camera's LCD display when the Focus Ring rotation is detected by the camera.

* Please set "MF Mode" to use this function.

* On some camera bodies, you can not use this function.

5. 5-Axis Image Stabilization

The SEPTON 40mm F2 E-mount lens is compatible with E-mount cameras with built-in multi-axis Image Stabilization.

● Specifications

Product Name	SEPTON 40mm F2
Focal Length	40mm
Maximum Aperture	F2
Minimum Aperture	F22
Lens Construction	6 groups 7 elements
Angle of View	57.3°
Aperture Blade	10
Minimum Focus	0.3m
Macro Ratio	1:5.3
Filter Size	Ø52mm
Maximum Diameter	Approx. Ø61.7mm
Length	Approx. 30.0mm
Weight	Approx. 165g
Mount	E-mount
Aperture Ring	Available (Manual Setting)(1/3 stop increments)
Electric Contact	Available
Manual Focus Assist	Available
Exif Data	Available
Auto Lens Correction	Possible

* Specification and information are subject to change without prior notice.

● Specifications

5-Axis Image Stabilization	Possible * only on camera body with 5-Axis Image Stabilization
Supplied Accessory	Front Cap, Rear Cap, Lens Hood

* Specification and information are subject to change without prior notice.